

CONDITIONED SHORT-CIRCUIT CURRENT – GDA/ABB

[kA eff. 1"] (380/415 V)

GDA at 43°C

Switch Model	160 A	250 A	400 A	500 A	630 A	800 A	1000 A
Sace Isomax S2 B	16						
Sace Isomax S2 N	35						
Sace Isomax S2 S	50						
Sace Isomax S3 N	35	35					
Sace Isomax S3 H	65	65					
Sace Isomax S3 L	85	85					
Sace Isomax S4 N	35	35					
Sace Isomax S4 H	65	65					
Sace Isomax S4 L	100	100					
Sace Isomax S5 N	35	35	35	35	35		
Sace Isomax S5 H	65	65	65	65	65		
Sace Isomax S5 L	100	100	100	100	100		
Sace Isomax S6 N	35	35	35	35	35	35	
Sace Isomax S6 S	50	50	50	50	50	50	
Sace Isomax S6 H	65	65	65	65	65	65	
Sace Isomax S6 L	100	100	100	100	100	100	
Sace Isomax S7 S	50	50	50	50	50	50	50
Sace Isomax S7 H	65	65	65	65	65	65	65
Sace Isomax S7 L	100	100	100	100	100	100	100
T Max T1 1P B	/						
T Max T1 B	16						
T Max T1 C	25						
T Max T1 N	36						
T Max T2 N	36						

CONDITIONED SHORT-CIRCUIT CURRENT – GDA/ABB

T Max T2 S	50						
T Max T2 H	70						
T Max T2 L	85						
T Max T3 N		36					
T Max T3 S		50					